Applicant: Andreas Norbert Wiswesser et al. Attorney's Docket No.: 05542-331003 / 3250C4

FISH & RICHARDSON

Serial No.: 10/722,716

Filed: November 25, 2003

Page : 2 of 6

## Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

## Listing of Claims:

1. (Original) A method of monitoring a substrate having a metal layer during chemical mechanical polishing, the method comprising:

polishing a metal layer of a substrate with a polishing pad; sweeping a sensor along a path across the substrate during the polishing step; generating a sequence of sensor measurements from the sensor as the sensor sweeps along the path;

associating each of the sensor measurements with a radial position on the substrate; dividing the sensor measurements into a plurality of radial ranges based on the radial positions; and

determining a characteristic of the metal layer for each radial range from the measurements associated with that radial range.

- 2. (Original) The method of claim 1, wherein polishing includes supporting the polishing pad on a support and moving the support relative to substrate.
- 3. (Original) The method of claim 2, wherein the sensor is secured to the support so that moving the support relative to the substrate causes the sensor to sweep along the path.
- 4. (Original) The method of claim 3, wherein the support comprises a platen and moving the support includes rotating the platen.

Applicant: Andreas Norbert Wiswesser et al. Attorney's Docket No:: 05542-331003 / 3250C4

Serial No.: 10/722,716

Filed: November 25, 2003

Page : 3 of 6

5. (Original) The method of claim 1, wherein generating a sequence of sensor measurements includes directing a light beam from the sensor to the substrate.

- 6. (Original) The method of claim 5, wherein generating a sequence of sensor measurements includes receiving a reflection of the light beam from the substrate to the sensor.
- 7. (Original) The method of claim 1, further comprising detecting a polishing endpoint using measurements from at least one of the radial ranges.
- 8. (Original) The method of claim 7, further comprising stopping chemical mechanical polishing when the endpoint is identified.
- 9. (Original) The method of claim 7, wherein detecting the polishing endpoint includes identifying a predetermined pattern from the measurements.
- 10. (Original) The method of claim 9, wherein the identifying step comprises comparing the measurements to a predetermined threshold.
- 11. (Original) The method of claim 9, wherein the sensor makes a plurality of sweeps across the substrate to generate a series of measurements.
- 12. (Original) The method of claim 11, wherein the identifying step comprises determining whether a series of measurements from the sensor have a downward trend.
- 13. (Original) The method of claim 11, wherein the identifying step comprises determining whether a series of measurements from the sensor have an upward trend.

Applicant: Andreas Norbert Wiswesser et al. Attorney's Docket No.: 05542-331003 / 3250C4

Serial No.: 10/722,716

Filed: November 25, 2003

Page: 4 of 6

- 14. (Original) The method of claim 11, wherein the identifying step comprises determining whether a series of measurements from the sensor have a flat trend.
- 15. (Original) The method of claim 1, wherein the associating step includes determining a time that the sensor crosses a midline of the substrate, and determining a position of the sensor at a measurement time from a difference between the measurement time and the time that the sensor crosses the midline of the substrate.
- 16. (Original) The method of claim 15, wherein the associating step includes determining a position of the carrier head from a carrier head sweep profile.
- 17. (Currently Amended) An apparatus for polishing a metal layer of a substrate, comprising:
  - a support to hold a polishing pad;
  - a carrier head to hold the substrate in contact with a surface of the substrate;
- a motor coupled to the support to cause relative motion between the substrate and the polishing pad;
- a sensor secured to the support to generate a sequence of sensor measurements as the sensor sweeps along a path; and
- a computer configured <u>and programmed</u> to associate each of the sensor measurements with a radial position on the substrate, divide the sensor measurements into a plurality of radial ranges based on the radial positions, and determine a characteristic of the metal layer for each radial range from the measurements associated with that radial range.
- 18. (Original) The apparatus of claim 17, wherein the sensor includes a light source to generate a light beam directed to the substrate and a detector to detect a reflection of the light beam from the substrate.

Attorney's Docket No.: 05542-331003 / 3250C4

Applicant: Andreas Norbert Wiswesser et al.

Serial No.: 10/722,716

Filed: November 25, 2003

Page : 5 of 6

19. (Original) The apparatus of claim 17, wherein the support comprises a rotatable platen.

20. (Original) The apparatus of claim 17, wherein the computer is configured to stop chemical mechanical polishing when an endpoint is identified.

21-25. (Cancelled)